

Kotohira System Battery Pack Datasheet

Introduction: BAT08, BAT16, BAT20 Rackmount battery pack (application UPS with DC voltage: 36V, 72V, 96V, 192V, 240V) are the standard battery pack we equipped for our single phase and three phase rackmount UPS with battery external model.

Customer can choose to configure the 12V 7AH or 12V 9AH Valved Lead Acid Maintenance Free batteries with good battery quality to ensure the safety and reliability of the UPS

1. BAT08 Photos & Specification:



BAT08 Specification:

Model	BAT08-007/3P	BAT08-009/3P	BAT08-007/6P	BAT08-009/6P	BAT08-007	BAT08-009
Physical Parameters						
Height	88mm 2U					
Width	438 mm 19"					
Depth	480mm					
Battery Internal	7AH	9AH	7AH	9AH	7AH	9AH
Battery quantity	3nos		6nos		8nos	
DC voltage	36Vdc		72Vdc		96Vdc	
Weight	11.8Kg	13.1Kg	17.7Kg	20.1Kg	21.5Kg	24.7Kg
Installation	Horizontal (Rackmount)					

2. BAT16/BAT20 Photos & Specification:



BAT16/BAT20 Specification:

Model	BAT16-007	BAT16-009	BAT20-007	BAT20-009
Physical Parameters				
Height	88mm 2U			
Width	438mm 19"			
Depth	680mm		860mm	
Battery	7AH	9AH	7AH	9AH
Internal				

Battery	16nos		20nos	
Quantity				
DC voltage	192Vdc		240Vdc	
Weight	41.5Kg	47.9Kg	49.3Kg	57.3Kg
Installation	Horizontal (Rackmount)			

Battery Specification:

Parameters	
Color	Black
Weight	0-40°C
Temperature	0-95% non-condensing
Storage	-15°C-45°C