ACS Series

10~20kVA 3/1 single phase Rack UPS



Power range

10~20kVA

Operation

3/1,online double conversion

Applications

Government, Finance, IT, Education, Transportation, Broadcasting, Medical, Energy, etc.

Characteristics

- Intelligent battery management.
- 3-level topology, high performance and efficiency.
- Online double conversion, full digital control.
- Output PF=1,high load adaptability.
- Wide range of input voltage tolerance.
- Adapt to half-wave load.
- Auto fault waveform recording.
- Self-aging function to save test energy.

Model		TS010LR	TS015LR	TS020LR
Rate Power		10kVA	15kVA	20kVA
Cold start		Default output 50/60Hz		
Input voltage range		190~499VAC(L-L)		
Input power factor		≥0.99		
Frequency range		40-70Hz		
Output frequency		50/60Hz,self adaption		
Output power factor		1		
Rate output		220/230/240VAC		
Load regulation		±1%		
Output THDu		≤1%,Linear load; ≤3%,non-linear load according to IEC62040-3		
Transfer time-INV to BYP		0ms		
Efficiency- normal mode		Max 95%		
Efficiency- ECO mode		98%		
Noise (1 meter)		<55dB	<62dB	<62dB
Overload (normal mode)		110%:10mins;125%:1min;150%:30 seconds		
Battery	Model	External batteries,16-24 settable		
	Quantity			
	Max charging	5A		
	Rate voltage	Default 192VDC,settable		
Crest factor		3:1		
Standard		RS232, RS485,EPO		
Option		AS400, SNMP card, Parallel kit, USB, 12A charger, Air filter, Single Input kit		
Dimension, W*D*H(mm)		440*730*173(4U)		
Weight(kg)		30		

Statement: The products will continue to be innovative and optimized, which may lead to asynchronized updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.